

# FLESSIBILI DN 8

FLESSIBILI PER RUBINETTERIA E SANITARI  
FLEXIBLES FOR FAUCETS AND SANITARIES









## DATI TECNICI - TECHNICAL DATA:

Tubo flessibile trecciato made in italy in acciaio Inox AISI 304 con interno in gomma alimentare EPDM utilizzato per il collegamento tra la rete idrica e la rubinetteria sanitaria o cassette W.C. e adatto a qualsiasi altro impiego sanitario. Tutti i flessibili sono raccordati con macchine automatiche ed il risultato è l'assoluta precisione di ogni pezzo prodotto per una garanzia di totale qualità.

*Made in Italy braided hose in AISI 304 stainless steel with internal in EPDM rubber, used for the connection between the water mains and the sanitary fittings or W.C. flushing tanks. All the hoses are produced with automatic machines and the result is the absolute precision of each produced piece for a total quality guarantee.*

## CARATTERISTICHE - FEATURES:

TEMPERATURA INSTALLAZIONE INSTALLATION TEMPERATURE 	PRESSIONE D'ESERCIZIO WORKING PRESSURE 	PORTATA A 3 BAR FLOW RATE AT 3 BAR 	TEMPERATURA D'IMPIEGO WORKING TEMPERATURE 	FORO MINIMO PASSAGGIO D'ACQUA FITTING INNER DIAMETER 	RAGGIO CURVATURA MINIMO MINIMUM BENDING RADIUS 
da -5°C a +90°C	10 BAR	29 lit/min	-5°C - +90°C	6 mm	30 mm

## MATERIALI - MATERIALS

TUBO HOSE 	Ø INTERNO INNER Ø 8 mm	Ø ESTERNO OUTER Ø 12 mm	Treccia 7 fili Ø 0,22mm in acciaio Inox AISI 304 Tubo interno: gomma EPDM atossico. 7 wires braid Ø 0,22mm in steel Inox AISI 304 Internal pipe: EPDM rubber, atoxic.
RACCORDI FITTINGS 	CW614N		Ottone CW614N e CW617N nichelato Brass CW614N and CW617N nickel plated
BUSSOLE SLEEVES 	Ø 14 mm		Acciaio Inox AISI 304 Stainless steel AISI 304